

# RAVEMUL O112 S

E01WD003 - 02/14

P 1 - 1

Ravemul O112 S is polyvinylacetate water dispersion suitable for textile finishing as well as the manufacture of wood, paper, board and building adhesives.

	Unit	Value	Method
<b>1. SUPPLY SPECIFICATIONS</b>			
Solid content	%	45±2	MVPF 01
Brookfield viscosity	(1) mPa.s	40000±10000	UNI EN ISO 2555
pH		4.5±0.5	ISO 976
<b>2. TYPICAL VALUES</b>			
Minimum film-forming temperature	°C	8	UNI 8490-14
Prevailing particle size range	µm	0.4÷4.0	MVANS 20
Dispersing system		polyvinyl alcohol	
Density at 23°C	kg/dm <sup>3</sup>	1.1	MVPF 18
Mechanical stability		excellent	MVAT 013
Rheological behaviour		pseudoplastic	

(1) RVT 20 rpm, spindle 7, 23°C

## APPLICATIONS

Wood, paper and building adhesives.  
Textile finishing.

## SPECIFIC PROPERTIES

Ravemul O112 S is particularly suitable to prepare low-cost adhesives for wood and its substitutes.  
It shows a good compatibility with fillers and is ideal to make parquet adhesives.

## PACKAGING

Ravemul O112 S is available in bulk and in 125 Kg or 50 Kg drums.

## STORAGE

Ravemul O112 S is stable for at least 6 months when stored between + 5°C and 40°C.

Data, information and suggestions are provided for guidance purpose only. VINAVIL EGYPT for Chemicals S.A.E. accepts no responsibility for the results obtained therefrom, nor for their utilization in infringement of possible patent rights. The analytical methods are available on request.